



**SRV600V2**

**SRV 600 V2**

# Introduction



# Surging Power Retro Style

The SRV 600 V2 merges aggressive muscular lines with avant-garde aesthetics, redefining the boundaries of traditional cruisers.

Powerful performance and agile handling come together seamlessly, transforming every acceleration into a dual feast for the eyes and senses.



# DESIGN Look



# Symphony of Sport and Style



A



B

## A. American Bobber Style

The American bobber embraces a stripped-down, lightweight design philosophy.

## B. Sword Sheath-Style Front Suspension

Accented with chrome air filter cover for a bold, dynamic visual impact.

## C. Round LED Headlight with Square Elements

Perfectly fuses retro and modern elements for unmistakable presence.

# SRV 6000 V2

## Product Features



# Thunderous Power, Soul-Stirring Rumble

The 550.4cc V-twin liquid-cooled engine delivers a maximum power output of 37.0 kW (50.3 PS) at 8,000 rpm and peak torque of 53.0 N·m at 6,500 rpm. Equipped with a standard slipper clutch that dramatically reduces downshift judder and shifting effort, it balances spirited performance with everyday comfort. The V-twin configuration unleashes a rich, throaty rumble and linear power delivery. Whether it's the deep pulse at idle or the exhilarating roar at high revs, every moment speaks to the pure joy of riding.



## V-Twin Engine

Maximum power

**37.0 kw (50.3 Ps)/8,000 rpm**

Maximum torque

**53.0N·m/6500rpm**

**Belt Drive**

# Sporty Rider Triangle ■

The **SRV 600 V2**'s riding position is thoughtfully crafted: the sport-oriented seat combined with forward-mounted footpegs creates a unique riding triangle, perfectly balancing cruising comfort with sporty handling demands. During aggressive riding, the carefully positioned footpegs provide solid support; during long rides, the ergonomically designed seat effectively reduces fatigue. This understated yet meticulously considered design embodies the essence of the SRV 600 V2.



# Comfort Assured Crafted in Every Detail



## A.Low Seat Height

705mm seat height, wide handlebars, and ergonomic controls combine to further enhance riding comfort.

## B.Spacious Dual Seats

Whether riding solo or with a passenger, enjoy exceptional comfort on every journey.

## C.Belt Drive

Experience smoother acceleration and deceleration with exceptionally quiet operation. The belt drive eliminates jerky engagement, delivering a refined and superior ride.

# Smooth Rides Comfort Assured

The sword sheath-style front suspension delivers precise steering feedback and robust support while efficiently absorbing bumps.





## ■ **Class-Leading Safety**

Front and rear disc brakes combined with dual-channel ABS + TCS system ensure stable braking performance while enhancing both safety and riding enjoyment.



## **Unleash the Distance Conquer the Extreme**

A generous 16L fuel tank provides a combined range of up to 400km, eliminating range anxiety.

# Thoughtful Tech Features



A



B

## A. Retro-inspired Round Color LCD Display

A minimalist retro design housing a modern technological core.

The display features a carefully designed visual layout with key riding data clearly presented at a glance, maintaining classic aesthetics while ensuring efficient and precise information access.

## B. Tip-over Safety Switch

Automatic engine shutdown after a fall, side stand shutdown function for safer riding.

# SRV 600 V2

## Specifications



### Engine

Type	2-Cylinder V, 8V DOHC, Liquid-Cooled
Bore*Stroke	70.5*70.5mm
Displacement	550.4cc
Max.Horsepower	35.0kW/8000rpm(47.6ps)
MAX.Torque	53.0N·m/6500rpm
Fuel system	EFI
Starting system	Electric
Clutch	Wet multi-plate
Transmission	6 Gears or AMT, Belt

### Chassis

Front suspension	Upside down telescopic forks
Rear suspension	Side mounted shock absorber
Front tyre	130/90-16
Rear tyre	180/65-16
Front brake	Disc ø320mm (ABS)
Rear brake	Disc ø360mm (ABS)

### Dimensions

Overall L*W*H	2190*830*1150mm
Wheel base	1555mm
Seat height	705mm
Ground clearance	120mm
Curb weight	205kg
Fuel capacity	16L

Available Colours:

Homologation: E5+

\* Due to the availability of personalized configuration options, the specifications of the purchased vehicle shall prevail.

\* Unless otherwise stated, all data presented on this page are test results obtained by the manufacturer under standard conditions and are provided for reference only. Actual performance may vary. Due to the availability of personalized configuration options, the specifications of the purchased vehicle shall prevail.